



**DOST-ASTI Bids and Awards Committee  
REQUEST FOR QUOTATION**

<b>Kind of Procurement Activity:</b>	Negotiated Procurement: Small-value Procurement		
<b>Deadline of Submission of Bids:</b>	Jun-30-2023, 2:00 PM		
<b>RFQ No.:</b>	23-06-4422	<b>Date:</b>	June-23-2023
<b>PR No.:</b>	GAA-23-05-16665	<b>Date:</b>	May-25-2023

The Department of Science and Technology (DOST) - Advanced Science and Technology Institute (ASTI), through its Bids and Awards Committee (BAC), intends to procure the enlisted item/s below. Bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, except otherwise specified in the requirements. Award may be considered for prospective bidder/s proven to be the single/lowest calculated and responsive quotation among all other quotations. Guidelines on the format of quotations and eligibility documents are listed below. Kindly follow the prescribed GUIDELINES to avoid DISQUALIFICATION.

Quotations may be submitted 1) manually to the BAC Secretariat at G/F DOST-ASTI Bldg., UP Technology Park Complex, CP Garcia Ave., UP Campus, Diliman, Quezon City or 2) sent via electronic mail at bac-sec@asti.dost.gov.ph. For further information, please contact the BAC Secretariat at +63 2 8249-8500 loc. 1206/1212.

Thank you.

**BAYANI BENJAMIN R. LARA**  
BAC Chairperson

NO.	TECHNICAL SPECIFICATIONS	QTY	UNIT	UNIT PRICE(Php)	TOTAL PRICE(Php)
1	<p><b>Various Items for Prototyping</b></p> <p>1. Objective</p> <p>1.1. Various items are for prototype development.</p> <p>1.2. Scope of service: supply and delivery of various components for prototyping</p> <p>2. Technical Specifications</p> <p>2.1. Edge Computing Board, 3pcs</p> <p>2.1.1. Module: Jetson Orin NX 8GB or better</p> <p>2.1.2. AI Performance: 70 TOPS or better</p> <p>2.1.3. GPU: 1024-core Ampere architecture with 32 Tensor Cores or better</p> <p>2.1.4. GPU Max Frequency: at least 765 MHz</p> <p>2.1.5. CPU: 6-core Arm Cortex-A78AE v8.2 64-bit CPU 1.5MB L2 + 4MB L3 or better</p> <p>2.1.6. CPU Max Frequency: at least 2GHz</p> <p>2.1.7. Memory: 8GB 128-bit LPDDR5 102.4GB/s or better</p> <p>2.1.8. DL Accelerator: 1x NVDLA v2 or better</p> <p>2.1.9. DLA Max Frequency: at least 614 MHz</p> <p>2.1.10. Vision Accelerator: 1x PVA v2 or better</p> <p>2.1.11. Storage: Supports external NVMe</p> <p>2.1.12. Video Encoder</p> <p>2.1.12.1. 1x 4K60 (H.265)   3x 4K30 (H.265) or better</p>	1	lot	289050.00	289,050.00

2.1.12.2. 6x 1080p60 (H.265) | 12x 1080p30 (H.265) or better  
2.1.13. Display: 1\* HDMI 2.1 or better  
2.1.14. CSI Camera: 2\* CSI (2-lane 15pin) or better  
2.1.15. Networking: 1\* Gigabit Ethernet (10/100/1000M) or better  
2.1.16. USB  
2.1.16.1. 4\* USB 3.2 Type-A (10Gbps) or better  
2.1.16.2. 1\* USB2.0 Type-C (Device Mode) or better  
2.1.17. M.2 Key M: 1\* M.2 Key M or better  
2.1.18. M.2 Key E: 1\* M.2 Key E or better  
2.1.19. Fan: 1\* 4 pin Fan Connector(5V PWM) or better  
2.1.20. CAN: 1\*CAN or better  
2.1.21. Multifunctional Port  
2.1.21.1. 1\* 40-Pin Expansion header or better  
2.1.21.2. 1\* 12-Pin Control and UART header or better  
2.1.22. RTC: RTC 2-pin, RTC socket (supports CR1220) or better  
2.1.23. Power: 9-19V  
2.1.24. Power Supply: DC 12V/5A(Barrel Jack 5.5/2.5mm)  
2.1.25. Temperature: -10°C~60°C  
2.1.26. Mechanical: approximately 130mm x120mm x 58.5mm  
2.1.27. Parts list  
2.1.27.1. 1x Jetson Orin NX 8GB or better  
2.1.27.2. 1x carrier board (J401) or better  
2.1.27.3. 1x 128GB NVMe SSD or better  
2.1.27.4. 1x Aluminum heatsink with fan  
2.1.27.5. 1x Aluminum case (black)  
2.1.27.6. 1x 12V/5A power adapter or better

## 2.2. Depth Camera, 2 pcs

2.2.1. Use Environment: Indoor/Outdoor  
2.2.2. Image Sensor Technology: Global Shutter  
2.2.3. Ideal Range: .6 m to 6 m or better  
2.2.4. Depth Technology: Stereoscopic  
2.2.5. Minimum Depth Distance (Min-Z) at Max Resolution: ~52 cm or better  
2.2.6. Depth Accuracy: <2% at 4 m or better  
2.2.7. Depth Field of View (FOV): 87° × 58° or better  
2.2.8. Depth Stream Output Resolution: Up to 1280 × 720 or better  
2.2.9. Depth Stream Output Frame Rate: Up to 90 fps or better  
2.2.10. RGB Frame Resolution: 1280 x 800 or better  
2.2.11. RGB Frame Rate: 30 fps or better  
2.2.12. RGB Sensor Technology: Global Shutter or better  
2.2.13. RGB Sensor FOV: 90° × 65° or better  
2.2.14. RGB Sensor Resolution: 1 MP or better  
2.2.15. Camera Module: RealSense Module D450 or better  
2.2.16. Vision Processor Board: RealSense Vision Processor D4 or better  
2.2.17. Form factor: Camera Peripheral  
2.2.18. Camera Dimension (Length × Depth × Height): 124 mm × 26 mm × 29 mm  
2.2.19. Connectors: USB-C 3.1 Gen 1 or better  
2.2.20. Mounting Mechanism  
2.2.20.1. One 1/420 UNC thread mounting point

2.2.20.2. Two M4 thread mounting points  
2.2.20.3. Tripod

2.3. Single Board Computer, 3pcs

2.3.1. Processor

2.3.1.1. 64bit hexa core processor Rockchip RK3399-T or better

2.3.1.2. Dual Cortex-A72, frequency 1.5Ghz with quad Cortex-A53, frequency 1.0Ghz or better

2.3.1.3. Mali T860MP4 GPU or better

2.3.1.4. OpenGL ES 1.1 /2.0 /3.0 /3.1 /3.2, Vulkan 1.0, Open CL 1.1 1.2, DX11 or better

2.3.2. Memory: 64bit dual channel LPDDR4@3200Mb/s, 4GB or better

2.3.3. Storage

2.3.3.1. eMMC connector or better

2.3.3.2. uSD slot supports up to 128G uSD card or better

2.3.4. Display

2.3.4.1. 2x micro HDMI, 1x HDMI 4Kp60, 1x HDMI 2Kp60 or better

2.3.4.2. MIPI DSI 4 lanes via FPC connector or better

2.3.5. Audio: 3.5mm Headphone Jack HD codec that supports up to 24-bit/96kHz audio or better

2.3.6. Camera: MIPI CSI 2 lanes via FPC connector, support up to 800MP camera(0.3mm pitch connector) or better

2.3.7. Wireless: WiFi5 / BT5 with external antenna(included) or better

2.3.8. USB

2.3.8.1. USB 3.0 OTG x1 hardware switch for host/device switch, upper one or better

2.3.8.2. USB 3.0 HOST x1 dedicated USB3.0 channel, lower one or better

2.3.8.3. USB 2.0 HOST x2 or better

2.3.9. Ethernet: GbE LAN with PoE support additional HAT is required for powering from PoE or better

2.3.10. IO

2.3.10.1. 1 x UART or better

2.3.10.2. 2 x SPI bus or better

2.3.10.3. 2 x I2C bus or better

2.3.10.4. 1 x PCM/I2S or better

2.3.10.5. 1 x SPDIF or better

2.3.10.6. 1 x PWM or better

2.3.10.7. 1 x ADC or better

2.3.10.8. 6 x GPIO or better

2.3.10.9. 2 x 5V DC power in or better

2.3.10.10. 2 x 3.3V power pin or better

2.3.11. Others

2.3.11.1. RTC battery connector for time backup or better

2.3.11.2. 2P PWM Fan header or better

2.3.12. Power

2.3.12.1. Supports USB Type C PD 2.0, 9V/2A, 12V/2A or better

2.3.12.2. Supports QC3.0/2.0 adapter, 9V/2A, 12V/1.5A or better

2.3.12.3. GPIO +5V - Power from GPIO pin2&4 or better

2.3.12.4. USB C 5V/3A or better

2.3.12.5. GPIO +5V - Power from GPIO pin2&4 or

	<p>better</p> <p>2.3.13. Size: approximately 85mm x 54mm</p> <p>2.4. Inverter - Pure Sine Wave, 2pcs</p> <p>2.4.1. Peak Power: 1000W or better</p> <p>2.4.2. Continuous Power: 500W or better</p> <p>2.4.3. Input Voltage: 12V</p> <p>2.4.4. Output Voltage: 220V ±10V</p> <p>2.4.5. Output Frequency: 60Hz</p> <p>2.4.6. Conversion Efficiency: at least 90%</p> <p>2.4.7. Compatible Voltage: 9.5V – 12V – 14.8V</p> <p>2.4.8. Output Waveform: Pure Sine Wave</p> <p>2.4.9. Product Size: approximately 220x98x55mm</p> <p>2.4.10. Weight: approximately 0.75kg</p> <p>2.5. Warning Light, 5pcs</p> <p>2.5.1. Type: LED Rotary</p> <p>2.5.2. Rated Voltage: 12V</p> <p>2.5.3. Rated Current: 120mA</p> <p>2.5.4. Installation method: screw fixing</p> <p>2.5.5. Dimension: approximately 102x155mm</p> <p>3. Warranty</p> <p>3.1. Supplier warrants the item against defects in manufacturing and shipping and delivery issues.</p> <p>3.2. Defective and incorrect items shall be replaced.</p> <p>3.3. Warranty Period: at least six months.</p> <p>4. Payment and Delivery Terms</p> <p>4.1. Price is inclusive of government taxes, delivery, etc.</p> <p>4.2. Supplier to provide breakdown of price per item.</p> <p>4.3. Delivery: 45 days upon issuance of NTP.</p> <p>4.4. To be delivered to UP NEC Room 409.</p>				
2	<p><b>Various Technical Supplies</b></p> <p>1. Objective</p> <p>1.1. Various technical supplies for research and development.</p> <p>1.2. Scope of service: supply and delivery of various technical supplies</p> <p>2. Technical Specifications</p> <p>2.1. Foldable Pill Storage, 5pcs</p> <p>2.1.1. Material: Plastic, BPA-free</p> <p>2.1.2. Three-fold, eight compartments or better</p> <p>2.1.3. Locking buckle</p> <p>2.2. Mobile Whiteboard</p> <p>2.2.1. Quantity: 1 pc</p> <p>2.2.2. Aluminum frame</p> <p>2.2.3. Size: 900 x 1200mm or better</p> <p>2.2.4. Material: Dry erase steel and fiberboard</p> <p>2.2.5. Foldable pen tray</p> <p>2.2.6. Caster wheels with brake</p> <p>2.2.7. Included items</p> <p>2.2.7.1. Mobile whiteboard</p>	1	lot	60150.00	60,150.00

- 2.2.7.2. 1 x eraser
- 2.2.7.3. 2 x whiteboard pen
- 2.2.7.4. 4 x magnets

2.3. Mobile TV Stand, 2pcs

- 2.3.1. Suitable for 32 – 70 inch TVs
- 2.3.2. Weight capacity: up to 100kg
- 2.3.3. Adjustable height
- 2.3.4. Adjustable angle
- 2.3.5. Adjustable trays
- 2.3.6. Wheel brakes

2.4. Metal File Set, 2 sets

- 2.4.1. For grinding and polishing of metallic and non-metallic materials
- 2.4.2. Material: Steel
- 2.4.3. Quantity per set: 10pcs
  - 2.4.3.1. Flat file
  - 2.4.3.2. Pointed flat file
  - 2.4.3.3. Half-round file
  - 2.4.3.4. Oval file
  - 2.4.3.5. Triangular file
  - 2.4.3.6. Single-sided file
  - 2.4.3.7. Round file
  - 2.4.3.8. Rounded file
  - 2.4.3.9. Square file
  - 2.4.3.10. Knife-shaped file

2.5. Heavy Duty Lifter Transport Tool, 2 sets

- 2.5.1. Material: Steel + ABS + PVC
- 2.5.2. Triangular plate: approximately 17.9x17.9x23cm
- 2.5.3. Tear strip length: approximately 34.5cm
- 2.5.4. Weight: approximately 2558g
- 2.5.5. Items included
  - 2.5.5.1. 4 x corner shifters
  - 2.5.5.2. 1 x lifting tool

2.6. Stainless Steel Tube, 20pcs

- 2.6.1. Stainless Steel Grade: 304
- 2.6.2. Length: 2ft
- 2.6.3. Thickness: 1.2mm
- 2.6.4. Diameter: 1/2"

2.7. Connector - Molex Receptacle Housing, 100pcs

- 2.7.1. Molex 00503755033 or equivalent
- 2.7.2. Connector Type: Receptacle
- 2.7.3. Contact Type: Female Socket
- 2.7.4. Number of Positions: 3
- 2.7.5. Pitch: 0.098" (2.50mm)
- 2.7.6. Number of Rows: 1
- 2.7.7. Mounting Type: Free Hanging (In-Line)
- 2.7.8. Contact Termination: Crimp
- 2.7.9. Fastening Type: Locking Ramp

2.8. Connector - Molex Contact, 100pcs

- 2.8.1. Molex 0008701039 or equivalent
- 2.8.2. Contact Termination: Crimp
- 2.8.3. Wire Gauge: 22-28 AWG
- 2.8.4. Contact Finish: Tin

2.9. Connector - JST Receptacle Housing, 100pcs

- 2.9.1. JST EHR-3 or equivalent
- 2.9.2. Connector Type: Receptacle
- 2.9.3. Contact Type: Female Socket
- 2.9.4. Number of Positions: 3
- 2.9.5. Pitch: 0.098" (2.50mm)
- 2.9.6. Number of Rows: 1
- 2.9.7. Mounting Type: Free Hanging (In-Line)
- 2.9.8. Contact Termination: Crimp

- 2.10. Connector - JST Contact, 100pcs
- 2.10.1. JST ASEHSEH22k102 or equivalent
- 2.10.2. Contact End: Socket to Socket
- 2.10.3. Length: 4.00" (101.60mm)
- 2.10.4. Wire Gauge: 22 AWG
- 2.10.5. Contact Finish: Tin

- 2.11. Connector - Molex Receptacle Housing, 100pcs
- 2.11.1. Molex 0009503021 or equivalent
- 2.11.2. Connector Type: Receptacle
- 2.11.3. Pitch: 0.156" (3.96mm)
- 2.11.4. Number of Rows: 1
- 2.11.5. Contact Termination: Crimp
- 2.11.6. Fastening Type: Locking Ramp

- 2.12. Connector - Molex Contact, 100pcs
- 2.12.1. Molex 008520072 or equivalent
- 2.12.2. Contact Termination: Crimp
- 2.12.3. Wire Gauge: 18-24 AWG
- 2.12.4. Contact Finish: Tin

- 2.13. Metal Insert - M3, 2 packs
- 2.13.1. Material: Brass
- 2.13.2. Size: M3
- 2.13.3. Type: Heat-set, Counter Threaded
- 2.13.4. Quantity per pack: 100pcs
- 2.13.5. Suitable for thermoplastics

- 2.14. Metal Insert - M5, 2 packs
- 2.14.1. Material: Brass
- 2.14.2. Size: M5
- 2.14.3. Type: Heat-set, Counter Threaded
- 2.14.4. Quantity per pack: 100pcs
- 2.14.5. Suitable for thermoplastics

- 2.15. M3 Screw Set, 1 set
- 2.15.1. Head: Hex Socket Pan Head
- 2.15.2. Size/Material: M3, Stainless Steel
- 2.15.3. Quantity per size
- 2.15.3.1. 110 pcs 4mm screws
- 2.15.3.2. 110 pcs 5mm screws
- 2.15.3.3. 110 pcs 6mm screws
- 2.15.3.4. 110 pcs 8mm screws
- 2.15.3.5. 110 pcs 10mm screws
- 2.15.3.6. 110 pcs 12mm screws
- 2.15.3.7. 110 pcs 14mm screws
- 2.15.3.8. 110 pcs 16mm screws
- 2.15.3.9. 110 pcs 18mm screws
- 2.15.3.10. 110 pcs 20mm screws
- 2.15.3.11. 110 pcs 25mm screws
- 2.15.3.12. 110 pcs 30mm screws
- 2.15.4. 110pcs nuts

2.15.5. 300pcs flat washers

2.15.6. 100pcs lock nuts

2.16. M5 Screw Set, 1 set

2.16.1. Head: Hex Socket Cap Head

2.16.2. Size/Material: M5, Stainless Steel

2.16.3. Quantity per size

2.16.3.1. 20pcs 6mm screws

2.16.3.2. 20pcs 8mm screws

2.16.3.3. 20pcs 10mm screws

2.16.3.4. 20pcs 12mm screws

2.16.3.5. 20pcs 14mm screws

2.16.3.6. 20pcs 16mm screws

2.16.3.7. 20pcs 18mm screws

2.16.3.8. 20pcs 20mm screws

2.16.3.9. 20pcs 25mm screws

2.16.3.10. 20pcs 30mm screws

2.16.3.11. 20pcs 35mm screws

2.16.3.12. 20pcs 40mm screws

2.16.4. 100pcs nuts

2.16.5. 300pcs flat washers

2.16.6. 60pcs lock nuts

2.17. Tapping Tool Set, 1 set

2.17.1. 5-pc Metric tapping screw

2.17.2. Size: M3, M4, M5, M6, M8

2.17.3. Material: Steel

2.18. T-Nut - M3, 1 pack

2.18.1. Suitable for 2020 profile

2.18.2. Material: Carbon steel 4.8 class or better

2.18.3. Surface treatment: Nickel plated

2.18.4. Thread size: M3

2.18.5. Quantity per pack: at least 90pcs

2.19. T-Nut - M5, 1 pack

2.19.1. Suitable for 2020 profile

2.19.2. Material: Carbon steel 4.8 class or better

2.19.3. Surface treatment: Nickel plated

2.19.4. Thread size: M5

2.19.5. Quantity per pack: at least 90pcs

2.20. Webcam

2.20.1. Quantity: 1 unit

2.20.2. Full-HD Video Calling

2.20.3. Full-HD Glass Lens (5-element glass lens)

2.20.4. Equipped with automatic HD autofocus and light correction

2.20.5. Dual Microphones

2.20.6. Max Resolution: 1080p/30fps - 720p/30fps or better

2.20.4. Focus type: autofocus

2.20.5. Built-in mic: stereo

2.20.6. Tripod-ready universal clip fits laptops, LCD or monitors

2.20.7. Cable length: at least 5 ft. (1.5 m)

2.20.8. Field of view: 78 degrees or better

2.21. Step-Down Transformer, 1 unit

2.21.1. Input: 220VAC 60Hz

2.21.2. Output: 110VAC 60Hz

2.21.3. Capacity: at least 500W  
 2.21.4. Coil: 99.9% Copper  
 2.21.5. Outlet: at least one  
 2.21.6. On/Off Switch: yes  
 2.21.7. Fuse: yes  
 2.21.8. Powder-coated metal casing

2.22. Ferrule Kit, 1 set  
 2.22.1. Ferrule Crimping Tool  
 2.22.1.1. HSC8 6-6A compatible  
 2.22.1.2. Crimping Range: 0.25 - 6mm<sup>2</sup> or better  
 2.22.1.3. Wire Range: AWG23 – AWG10 or better  
 2.22.2. 1,200-piece Ferrule Kit  
 2.22.2.1. Plastic Case  
 2.22.2.2. at least 200pcs E0508 White Ferrule size 0.5 mm<sup>2</sup>  
 2.22.2.3. at least 200pcs x E7508 Grey Ferrule size 0.75 mm<sup>2</sup>  
 2.22.2.4. at least 200pcs x E1008 Red Ferrule size 1.0 mm<sup>2</sup>  
 2.22.2.5. at least 250pcs x E1508 Black Ferrule size 1.5mm<sup>2</sup>  
 2.22.2.6. at least 250pcs x E2508 Blue Ferrule size 2.5mm<sup>2</sup>  
 2.22.2.7. at least 50pcs x E4009 Grey Ferrule size 4mm<sup>2</sup>  
 2.22.2.8. at least 25pcs x E6012 Yellow Ferrule size 6mm<sup>2</sup>  
 2.22.2.9. at least 25pcs E10-12 Red Ferrule size 10mm<sup>2</sup>

2.23. Air Duster, 1 unit  
 2.23.1. Air Thrust: 70 m/s or better  
 2.23.2. Motor Maximum Speed: 60,000 RPM or better  
 2.23.3. Full grip handle  
 2.23.4. Built-in LED: Yes  
 2.23.5. Charging port: USB Type C  
 2.23.6. Items included  
 2.23.6.1. Air Duster  
 2.23.6.2. Brush  
 2.23.6.3. Nozzle  
 2.23.6.4. USB Cable

3. Warranty  
 3.1. Supplier warrants the item against defects in manufacturing and shipping and delivery issues.  
 3.2. Defective and incorrect items shall be replaced.  
 3.3. Warranty Period: at least six months.

4. Payment and Delivery Terms  
 4.1. Price is inclusive of government taxes, delivery, etc.  
 4.2. Supplier to provide breakdown of price per item.  
 4.3. Delivery: 45 days upon issuance of NTP.  
 4.4. To be delivered to UP NEC Room 409.

3	<b>Fiber Optic Cable</b> 1. Objective 1.1. Fiber optic cable for data networking.	1	pc	30000.00	30,000.00
---	---	---	----	----------	-----------



1.2. Scope of service: supply and delivery of fiber optic cable

2. Technical Specifications

2.1. Length: at least 200m

2.2. Termination: LC-LC

2.3. No. of cores: at least two

2.4. Suitable for outdoor use

3. Warranty

3.1. Supplier warrants the item against defects in manufacturing and shipping and delivery issues.

3.2. Defective and incorrect items shall be replaced.

3.3. Warranty Period: at least six months.

4. Payment and Delivery Terms

4.1. Price is inclusive of government taxes, delivery, etc.

4.2. Supplier to provide breakdown of price per item.

4.3. Delivery: 45 days upon issuance of NTP.

4.4. To be delivered to UP NEC Room 409.

**TOTAL APPROVED BUDGET FOR THE CONTRACT (ABC):**

**Php 379,200.00**

**GUIDELINES**

**A. Content and Format of Quotations**

1. *The Quotation/s must include the RFQ Number or the PR Number indicated above*
2. *Bidders must specify the BRAND NAMES and MODEL NAMES/NUMBER for the following goods:*
  - a. *Computer and electronic equipment and its accessories or peripherals*
  - b. *Software applications, programs, and digital licenses*
  - c. *Commercial off-the-shelf electronic devices or components*
3. *The Quotation/s must indicate the registered business name of the company (or individual), business address and contact number. It must also include the full name and signature of the company's authorized representative.*
4. *BIR Certificate of Registration for new DOST-ASTI suppliers.*

**B. Eligibility Requirements**

*Pursuant to Annex "H" or Consolidated Guidelines for the Alternative Methods of Procurement of the 2016 Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184, the following documents shall be submitted except for Repeat Order, Shopping under Section 52.1(a), and Negotiated Procurement under Sections 53.1 (Two-Failed Biddings), and 53.5 (Agency-to-Agency):*

**For Procurement of Goods**

1. *Upon submission of quotation*
  - a. *Valid PhilGEPS Registration Number / Organization ID*
  - b. *Valid Mayor's/Business Permit*
2. *Upon issuance of Notice of Award (NOA)*
  - a. *Omnibus Sworn Statement (shall be required only for procurement projects with ABC above P50,000.00)*
  - b. *Income/Business Tax Return (For ABCs above P500,000.00)*

**For Procurement of Infrastructure**

1. *Upon submission of quotation*
  - a. *Valid PhilGEPS Registration Number / Organization ID*
  - b. *Valid Mayor's/Business Permit*
  - c. *Valid PCAB License*
2. *Upon issuance of NOA*

- a. *Omnibus Sworn Statement (shall be required only for procurement projects with ABC above P50,000.00)*
- b. *Income/Business Tax Return (For ABCs above P500,000.00)*

*\*Requirements under Section 53.6 (Scientific, Scholarly or Artistic Work, Exclusive Technology and Media Services) of the revised IRR of RA No. 9184 will not apply to artists such as singer, performer, poet, writer, painter and sculptor who are engaged in business.*

*\*\*Requirements under Section 53.10 (Lease of Real Property or Venue) of the revised IRR of RA No. 9184, specifically Mayor's/Business Permit, PhilGEPS Registration Number and Income/Business Tax Return will not apply to government agencies as lessors.*

*\*\*\*For methods of procurement requiring Mayor's Permit and PhilGEPS Registration Number, valid Certificate of Platinum Membership may be submitted in lieu of the said documents.*

### **C. Terms and Conditions**

1. *Additional requirements, if necessary, may be requested by the BAC depending on the item to be bid;*
2. *All transactions are subject to creditable withholding tax and final Value Added Tax or percentage tax per revenue regulation/s of the BIR;*
3. *Liquidated damages of at least equal to one-tenth of one percent (0.001) of the cost of the unperformed portion for every day of delay shall be imposed by the DOST-ASTI pursuant to Section 68 of the revised IRR of RA No. 9184; and*
4. *The DOST-ASTI reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.*